

# KX-T7775

## Premium Doorphone

Panasonic has gone a step further with the latest design of the new KX-T7775 Doorphone. With its elegant look and superior acoustic performance, the new Doorphone is a must have!

Suitable for both home and office use, the Doorphone will make sure your visitors are not left waiting, and it allows them to easily speak to whomever they need to on the premises.

The Doorphone has a selection of highly appealing, optional, interchangeable faceplates that will make a nice match with almost any decor, an illuminated button for low light front door areas or evening visitors and the capability to operate an existing doorbell chime.


- **Wall Mounted or Recessed Installation**
- **Interchangeable Metal Faceplates**
- **Illuminated Button with Blue LED**
- **Standard Doorbell Control**
- **Two-Way Conversation Between Any PBX Extension and Doorphone**



**Panasonic ideas for life**

## Installation Options

The KX-T7775 has two mounting options



### 1. Surface Mounting.

The Doorphone can be easily mounted onto most flat surfaces.



### 2. Recessed Mounting.

For a more appealing and professional installation the KX-T7775 can be recessed mounted. It fits directly into most plastic electrical boxes.

## Faceplate Options

A range of stylish metal faceplates are available:



Brushed Steel  
KX-A402

Polished Brass  
KX-A401

## Compatibility

The KX-T7775 is compatible with the following Panasonic PBX Systems:

Model	Compatibility	Option Card Needed
KX-TA308	Yes	Built In
KX-TA624	Yes	KX-TA62460
KX-TA824	Yes	KX-TA82461
KX-TA1232	Yes	KX-TA123260
KX-TAW848	Yes	KX-TAW84861
KX-TD816	Yes	KX-TD160 / KX-TD161
KX-TD1232	Yes	KX-TD160 / KX-TD161
KX-TDA50	Yes	KX-TDA5161
KX-TDA100	Yes	KX-TDA0161
KX-TDA200	Yes	KX-TDA0161
KX-TD500	Yes	KX-T96161

## Dimensions

Small compact design.



## KX-T7775 Specifications

Power	AC Adapter Input / Output	110V 60Hz / 24V 300mA	
	Doorphone (DP) Input*1 / Output	12V 60mA / 24V 1A*2	
Cable Diameter / Wiring Distance From PBX		AWG 26 / 689 ft.	
		AWG 24 / 1,115 ft.	
		AWG 22 / 1,640 ft.	
Illuminated Button		Yes	
Wall Mountable		Yes	
Recess Mountable		Yes	
Connections	Power Module	RJ11 Input	Tip / Ring DP1 from PBX
		DC Input	Power Supply DC +/-
		Terminal Block Output	Tip / Ring DP1 to KX-T7775
	Doorphone	Terminal Block Output	Tip / Ring DP1 from Module
Terminal Block Output		Doorbell In	
		Doorbell Out	
Dimensions (H x W x D)		5.1" x 3.3" x .20"	
Weight		.87 lbs.	

\*1 Tip and Ring Voltage from Power Module

\*2 Voltage across DoorBell Terminal